Variable-Resolution CESM (VR-CESM)

Annual CESM Tutorial, 2024

Adam R. Herrington

Project Scientist II Climate and Global Dynamics Laboratory, National Center for Atmospheric Research





Part 1: What is VR-CESM? Why use it? How to use it.



What is VR-CESM?

Variable-resolution is CESM's label for static mesh refinement in CAM (also referred to as regional refinement)

NCAR CESM Tutorial 2024

NCAR



There are various grid refinement approaches:

- Domain Nesting high-resolution limited area model occupies a portion of a global model
- Static Mesh Refinement refine a region of the global grid in the same model
- Adaptive Mesh Refinement refine moving features in the same model



Visualizations:

https://youtu.be/3APH7vJnwR8 https://youtu.be/3We_Mz-yaB8 https://www.youtube.com/watch?v=zFE ABDQILRs

Why VR-CESM?

The appeal of VR-CESM is the ability to simulate high-resolution in a global model at an affordable cost. The steal a phrase - it makes the impossible, possible.



FIG. 10. Normalized wall clock time for idealized tropical cyclone simulations in the globally uniform mesh (light blue) and the variable-resolution grid (pink). The dashed lines indicate the theoretical scaling assuming model run time scales linearly with number of mesh elements.





NCAR

UCAR



CAM support for VR-CESM





MPAS-A dynamical core

- Developed at MMM (c. 2013)
- Recently ported to CESM2.3+
- Centroidal Voronoi meshes
- Non-hydrostatic





Spectral-element dynamical core

- Jointly developed by NCAR & DOE (HOMME)
- Hydrostatic version supported in CESM2.0
- Cubed-sphere mesh
- Three VR grids run out-of-the-box in CESM2.3+



see cam6.4 users guide for instructions on running: https://ncar.github.io/CAM/doc/build/html/users_guide/atmosph eric-configurations.html#cam-developmental-compsets



What needs to be changed when running VR-CESM?

When increasing horizontal resolution in a global model, one needs to:

- 1. Reduce the strength of numerical filters
 - Less diffusion at higher-resolution
 - VR-CESM uses a scale-aware tensor hyper-viscosity
- 2. Reduce time-steps
 - Dynamical core time-step for stability
 - Physics time-step for physical realism

3. Increase the resolution of boundary conditions

- Topography boundary conditions need ~2dx length-scales smoothed-out (i.e., rougher terrain at hi-res)
- Resolve complex land surface type boundaries (coastlines, ice sheet margins, mountain glaciers)
- Emissions datasets for resolving point sources concentrated over urban centers

NCAR



You can run VR-CESM too! But you need to know how to regrid model output to analyze your simulations



Part 2: Regridding



Structured vs. Unstructured grids



PS (time,lat,lon)

NCAR

- 2D structured coordinate lat-lon
- We are all familiar with this; we derive the equations of motion in this coordinate!

Zonal mean - average over lon Stream function - $u = \frac{\partial \psi}{\partial y}$, $v = -\frac{\partial \psi}{\partial x}$



PS (time,ncol)

- 1D unstructured coordinate ncol
- An index associated with each grid column
- Allows for flexible grid structures

Plotting - NCL, Python can create map plots from unstructured arrays
Zonal mean - remap to lat-lon grid
Stream function - remap to lat-lon grid

How to regrid?

Method 1: Regrid entire netCDF history files

- Easier, but it takes up lots of storage space.
- Performed using command line packages (NCO, CDO).
- □ Usually requires a "mapping weights file" as input. For NCO,

ncremap -m <path-to-wgtfile> in.nc out.nc

Method 2: Regrid arrays on the fly in analysis scripts

- The more practical and sustainable approach.
- Invoke libraries/functions in your preferred analysis language (Python, NCL, MATLAB)
 - □ Internal regrid routines that don't require a mapping weights file (less accurate).
 - Internal regrid routines that require a mapping weights file (more accurate). For Python, load xESMF library

```
read_weights(filename, n_in, n_out)
apply_weights(weights, indata, shape_in, shape_out)
```

NCAR

How to generate a mapping weights file?

Define destination grid

- What grid do you want to regrid to?
- □ Should be ~equal res. (or coarser) than the source grid.
- 2 Locate source and destination grid file. On Derecho,
 - SCRIP grid files: /glade/campaign/cesm/cesmdata/inputdata/share/scripgrids/
 - ESMF mesh files: /glade/campaign/cesm/cesmdata/inputdata/share/meshes/
- 3 Generate mapping weights file using source and destination grid files
 - Command line TempestRemap (<u>https://github.com/ClimateGlobalChange/tempestremap</u>)
 - Command line ESMF. On Casper (and default intel libraries),
 - module load mpi-serial/2.3.0
 - module load esmf/8.5.0
 - **module show esmf/8.5.0** \Box shows the \$PATH to the executables

• • •

\$PATH/ESMF_RegridWeightGen -s <src-gridfile> -d <dst-gridfile> -m <method> -w <wgts-filename>



Part 3: Applications



Response of N. Atlantic storms to SST anomalies

20

Journal of Advances in JAMES Modeling Earth Systems*

Research Article 🔂 Open Access 💿 😱

Resolving Weather Fronts Increases the Large-Scale Circulation Response to Gulf Stream SST Anomalies in Variable-Resolution CESM2 Simulations

Robert C. J. Wills 🔀, Adam R. Herrington, Isla R. Simpson, David S. Battisti

First published: 15 July 2024 | https://doi.org/10.1029/2023MS004123

- 1° synoptic fronts are represented as a single feature
- 1/4° multiple convective elements form the cold front
- 1/8° lots of convective elements form the cold and warm fronts
 - Deeper circulations transport heat and momentum upwards and polewards
 - Feeds back on the large-scale to give an NAO-like response



NCAR

Wills et al. (2024), JAMES

Greenland Surface Mass Balance: AMIP Experiments

The Greenland Ice Sheet (GrIS) is an important component of the Earth System, but challenging to resolve at 1°





- GrIS Surface Mass Balance (SMB) is the integrated precipitation minus runoff+evap+subl
- Precipitation and melting processes are ~continuously improved from 2° and 1/8° and you can do a pretty good job with 1/4°

NCAR

UCAR

Herrington et al. (2022), JAMES

Greenland Clouds & Precipitation



1-2° models are missing clouds around the coastlines, and the interior is too cloudy

NCAR

UCAR



Model Topography and Flat Ice Sheets

- Model topography is smoothed –smooth out grid scale features so we don't generate 2dx modes (dx=grid spacing)
- Results in a flat ice sheet in 1-2° models, with storms penetrating far too deep into the ice sheet interior (Pollard 2000, CD)





Difference from ERA5 topography (m)



Figure from Waling et al., in press. The topography generation software (<u>https://github.com/NCAR/Topo</u>) is described in Lauritzen et al. 2015, GMD.

NCAR

UCAR

ARCTIC ¹/₄° VR grid: Idealized Warming Experiment

Here, we couple the ARCTIC grid to POP2 & CISM2, re-tune the model and test:

Is the GrIS *response* different between 1° (f09) and 1/4° (ARCTIC)?

f09

- f09 CESM2.1-CMIP6*
- f09 CESM2.1-no hacks



ARCTIC



ARCTIC ablation area increases less when the ELA rises. This is because the margins of the ice sheet are steeper, and more realistic at 1/4°.

ELA = Equilibrium Line Altitude

GrIS sea level contribution in the experiments

200 Year

100

1000

800

400

200

GrIS GMSLR (mm) 600

300

Yin et al., in review *Muntjewerf et al. 2020

Any Questions?



Extra Slides



What needs to be changed when running VR-CESM?

When increasing horizontal resolution in a global model, one needs to:

- 1. Reduce the strength of numerical filters
 - Less diffusion at higher-resolution
 - VR-CESM uses a scale-aware tensor hyper-viscosity
- 2. Reduce time-steps
 - Dynamical core time-step for stability
 - Physics time-step for physical realism
- 3. Increase the resolution of boundary conditions
 - Topography boundary conditions need ~2dx length-scales smoothed-out (i.e., rougher terrain at hi-res)
 - Resolve complex land surface type boundaries (coastlines, ice sheet margins, mountain glaciers)
 - Emissions datasets for resolving point sources concentrated over urban centers



